

### SE Single Sided Outdoor Case

Single sided wall mounted case. Case supplied with multi-angle bracket.  
 Fixings not supplied. The case is suitable for commercial outdoor applications made with rugged steel and toughened glass fronts, rated: EN 60529 IP65 - NEMA 4x European Railway Standard. The standard finish is silver powder coating.  
 Outdoor use with ultra bright red or yellow LED with high resolution display characters suitable for viewing in direct sunlight.  
 Automatic brightness control reduces display brightness at night.


### Weatherproof Standard

The SE range of clock cases are certified to IP65 - NEMA 4x and have been independently certified to conform with the Railway EMC Standard:  
 EN 50121-4:2000  
 EN 60529 - dust and water protection  
 EN 60068 -2-1 - cold temperature operation

### 4010E.220.xx.SE for wet in- or outdoor areas

12/24 Hour Display  
 Red or green or ultra red or ultra yellow LED  
 220mm Figures: Viewing Distance: 120m  
 Automatic Daylight Saving Changes  
 Automatic Dimming  
 Alternating Time & Date Capability  
 Start/Stop Watch Function (with supplied infra-red Controller)  
 Temperature display (with optional temperature probe)  
 Stand-alone or networking  
 Built in Quartz Crystal with accuracy of 0.1 sec/day  
 240VAC 50 Hz mains supply with battery back-up  
 Optional 24VDC power supply:  
 Continuous Load: approx. 2A at maximum brightness and displaying 0, 6 and 8 characters  
 Max. Inrush Current: approx. 12A for very short periods

Model	LED colour	Case Size L x H x D
4010E.220.UR.SE	Ultra Red	1166 x 370 x 78
4010E.220.UY.SE	Ultra Yellow	(118 with bracket)



### Synchronisation

The 4010E can be synchronised from following external signals:

- w482 Time Code
- DCF Time Code
- GPS Time Code

JOB NO.:		TITLE	 <small>A.B.N. 69 086 651 014</small> P.O. Box 115 - 18 Rose Street ANNANDALE NSW 2038 Ph: +61 2 8205 0575 Fax: +61 2 9571 9754 Email: sales@hertzelectronics.com.au Web: www.hertzelectronics.com.au
DATE:		<b>4010E.220.xx.SE</b> <b>Digital LED Clock</b> <b>in IP65 weather proof</b> <b>surface mounting case</b>	
DWN:		CUSTOMER:	